MAB 825 / MAB 345 SE The classic among the large BDS

The classic among the large BDS magnetic core drilling machines. For core drilling up to Ø 100 mm and 110 mm cutting depth.

WELCOME TO THE TOP CLASS

Entry to the top class with strong output and a high degree of flexibility. Suitable for twist drilling, reaming, countersink and tapping.

Overheating protection
Magnet indicator
Quick-change drilling system
Permanent internal lubrication
Swivel hase adjustment device for MAB 845 SB

Swivel base adjustment device for MAB 845 SB (More information on page 9)

MAB 825/MAB 845 SB

Motor output	1,800 W
Voltage	230 V AC, 50 – 60 Hz
Stroke	255 mm
Magnet dimensions	110 x 220 x 54 mm
Weight	25 kg
Quick-change drilling system	KEYLESS, 19 mm (3/4")
Industrial arbor	MT 3, 32 mm (1 1/4")
Spindle taper	MT 3
Gear 1 range: 40 – 110 rpm	Gear 2 range: 65 – 175 rpm
Gear 3 range: 140 – 360 rpm	Gear 4 range: 220 – 600 rpm
Safety clutch	
Permanent internal lubrication	
Torque control	\checkmark
Full wave control electronics	1
Magnet indicator	
Overheating protection	
Clockwise/anticlockwise rotation	
Carbon brush wear indicator	~
MAB 825 230 V	MAB 825 110/125 V
MAB 845 SB 230 V	
	MAB 845 SB 110/125 V

Included in delivery

1 Magnetic core drilling machine

- 1 KEYLESS quick-change drilling system 19 mm Weldon (3/4")
- 1 Industrial arbor ZIA 332-KN, 32 mm Weldon (1 1/4 ")
- 1 Ejector pin ZAK 075, 090, 100, 120
- 1 Carry case on wheels
- 1 Safety lashing strap
- 1 Offset screwdriver size 6
- 1 Ejector drift MT 3
- 1 Operating instructions

Core drill	Twist drillReamerCountersinkTapping
Max. Ø 100 mm Cutting depth: 30 - 55 - 75-110 mm	Ø 31.75 mm Ø 31.75 mm Ø 50 mm M30 1





Carbon brush wear indicator

25

MAR 845