

SMART ARC-300-D



Single Phase



Arc Force



Hot Start

Key Features

- Digital display meter
- Built-in hot start/anti-stick
- Arc-force
- Dual voltage 230V/415V
- Suitable for 6013, 7015 and 7018 electrode welding
- Continuous welding at 25 °C ambient temperature



Technical Specification

Model	SMART ARC-300-D	
Rated input voltage	AC230V±15%	AC415V±15%
Rated input power capacity (kVA)	16	
Rated duty cycle	25%	
No-load voltage (V)	71 (AC230 V)	63 (AC415 V)
Welding current range (A)	20~300	
Overall efficiency (%)	85	
Protection class	IP21S	
Power factor (cosφ)	0.7	
Insulation class	H	
Standard	EN60974-1	
Noise (dB)	<70	
Dimensions (mm)	383 X 162 X 307	
Weight (Kg)	5	
Applicable electrode (mm)	1.6-5	

*The company reserves the right to change the specification and images without prior notice.

Accessories

- 1 set electrode holder: 200A-16mm²(3m) 35-50
- 1 set earth clamp: 300A-16mm²-DKJ35-50 (1m)



Authorised Dealer

JASIC TECHNOLOGY INDIA PVT. LTD
New Delhi (India)